

Battery powered tug specification sheet

A single user can move heavy trolleys and wheeled equipment safely with Electrodrive's battery operated tugs.



Tug Compact

Tug Rise

Tug Axis 1T

Tug Axis 2T

Tug Axis 4T

Tug Axis 5T

Tug Tough 10T

	Tug Compact	Tug Rise	Tug Axis 1T	Tug Axis 2T	Tug Axis 4T	Tug Axis 5T	Tug Tough 10T	
Features	Tug capacity	500 kg	1000 kg	1000 kg	2000 kg	4000 kg	5000 kg	10 000 kg
	Max. pulling force:							
	• Flat ground	20 kg	240 kg	40 kg	80 kg	160 kg	200 kg	400 kg
	• Up a 6° ramp	6 kg	40 kg (15° ramp)	12 kg	24 kg	48 kg	60 kg	120 kg
	Speed mode	Three speed settings						
	Max. speed	up to 5 km/h	up to 3 km/h	up to 5 km/h	up to 5 km/h	up to 3 km/h	up to 3 km/h	up to 2.5 km/h
Dimensions (L/W/H)	1100/609/891 mm	1800/902/894 mm	1480/610/852 mm	1480/610/852 mm	1465/790/875 mm	1740/900/905 mm	1912/650/910 mm	
Unit weight	130 kg	750 kg	140 kg	160 kg	465 kg	630 kg	1000 kg	
Motor	Power (watts)	250	1500	250	400	450	600	1200
	Voltage (V)	24						
Batteries	Technology	MK-Gel (deep cycle, long-lasting, maintenance-free)						
	Amp-hour	33	100	42	42	70	70	70
	Voltage (V)	12	12	12	12	12	12	48
	No. of batteries	2						

Australia Wide Sales & Service

sales@materialshandling.com.au | www.materialshandling.com.au | 1300 65 00 35

MATERIALS
Handling PTY LTD *Working with ease...*